



AUTOMOTIVE PRODUCTS, INC.

**F-150 BED EXTENDER BRACKET  
INSTALLATION INSTRUCTIONS  
10-0030**

<b>QTY</b>	<b>PARTS KIT CONTENTS DESCRIPTION</b>	<b>TOOLS REQUIRED</b>
1	DRIVERS QUICK LATCH MOUNTING BRACKET	6 MM HEX KEY
1	PASSENGER QUICK LATCH MOUNTING BRACKET	
4	HOLD DOWN BRACKET	
4	M8 X 40 BUTTON HEAD CAP SCREW	
4	M8 NUTS	
4	M8 INTERNAL TOOTH LOCK WASHERS	

**F-150 QUICK LATCH MOUNTING BRACKET INSTRUCTIONS**

- Step 1. Remove contents from box and check for damage. Verify all parts against parts list. Read and understand instructions completely before installation.
- Step 2. Assemble brackets as shown in Figure 1.
- Step 3. With lever towards the tailgate side insert lower hold-down bracket through lower hole on d-pillar. (see Figure 2)
- Step 4. Insert upper hold-down bracket in upper hole of d-pillar. (see Figure 3)
- Step 5. Tighten bolts until approximately 1/2" of thread is left. (see Figure 4)
- Step 6. Center tabs on upper hold-down bracket in hole on d-pillar and tighten bolt while pulling outward to hold tabs in place. (see Figure 5)
- Step 7. Repeat for lower mounting bracket.
- Step 8. Check for interference with tailgate closed (Lever should be within 1/8" to 3/8" of tailgate). (see Figure 6)
- Step 9. Torque bolts to 90 in-lbs (7.5 ft-lbs).
- Step 10. Repeat steps 3-9 for other side.
- Step 11. Slide Bed Extender into brackets until it locks into place. (see Figure 7)
- Step 12. To remove extender either pull lever and pull upward on extender or rotate the extender 90° and then pull up on extender. (see Figure 8)

**F-150 BED EXTENDER BRACKET  
INSTALLATION INSTRUCTIONS,  
CONTINUED**

